

Bill of Materials Best Practices

We will accept your Bill of Materials (BOM) in any format. However, we ask that you use the following best practices that optimize our workflow and improve your overall experience.

ACCEPTED FILE FORMATS



Required	Optional		
Manufacturer Part NumberReference DesignatorsDescription Value PackageQuantity	 Manufacturer Name Vendor & Vendor Part Number Alternate Manufacturer Part Numbers Type 		

FORMATTING GUIDELINES

- Place all REFERENCE DESIGNATORS for identical parts in one cell¹. Quantity must match component count.
- Place the DESCRIPTION VALUE PACKAGE component descriptors in one cell.2
- Use full MANUFACTURER PART NUMBERS for all parts, including customer supplied parts.
- Place ALTERNATE PART NUMBERS on the same line in separate column to the right.
- Indicate the quantity of DO NOT INSTALL (DNI) PARTS in a separate DNI/DNP column³.
- Create an additional column for CUSTOMER SUPPLIED parts.
- Add NOTES in an additional column to the right⁴.
- Place all ASSEMBLY NOTES in a separate file.
- Do not use MERGED CELLS.

All reference designators in the same cell.

MFG PART #	DESCRIPTION VALUE PKG ²	BOROEY DES	QTY	DNI ³	NOTES ⁴
12065A330JAT2A	CAP 33pF 5V 1206	U1, U2	2		
C1206C104K3HACTU	CAP CER 0.1µF 25V 10% ULTRA STABLE X8R 1206	C10, C19, C26, C27, C28, C36, C57, C59	8		Must purchase from Digi-Key
VFT2045BP-M3/4W	Diode Schottkey 45V 20A ITO-220AC	D1	1		
CDH53-680JC	IND Power 68µH 1.21 Ohm	L1	0	1	
ERJ-1TNF1201U	RES 12k Ohm 1W 1% 2512 SMD	R5, R6	2		